



Marine & Offshore

Certificate number: 74483/A0 BV

File number: ACM 139/1905/6

Product code: 0226H

*This certificate is not valid when presented without the full attached schedule composed of 7 sections*

www.veristar.com

## TYPE APPROVAL CERTIFICATE

*This certificate is issued to*

**Hilti Corporation**  
SCHAAN - LIECHTENSTEIN

*for the type of product*

**MECHANICAL FASTENING SYSTEM**  
HILTI WELDED STUDS F-BT-MR MECHANICAL FASTENING SYSTEM

### Requirements:

BUREAU VERITAS Rules for the Classification of Steel Ships  
BUREAU VERITAS Rules for the Classification of Offshore Units  
BUREAU VERITAS Rules for the Classification of Naval Ships  
BUREAU VERITAS Rules for the Classification of Yachts

*This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.*

**This certificate will expire on: 25 May 2028**

**For Bureau Veritas Marine & Offshore,**

At BV HAMBURG, on 25 May 2023,

Heiko Lange

***This certificate was created electronically and is valid without signature***



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: <http://www.veristarm.com/veristarnb/jsp/viewPublicPdfTypepec.jsp?id=hw177fvffh>

BV Mod. Ad.E 530 June 2017

This certificate consists of 5 page(s)

## THE SCHEDULE OF APPROVAL

### 1. PRODUCT DESCRIPTION:

Mechanical fastening system: Hilti welded studs F-BT-MR.

The F-BT studs welded by Hilti CSF cordless stud fusion system. The Cordless Stud Fusion (CSF) process is a drawn arc stud welding process with shielding gas (process number 783) following EN ISO 14555. The purpose of Cordless Stud Fusion (CSF) is to weld studs to steel.

The Hilti F-BT mechanical fastening system comprises the surface preparation equipment, the stud fusion equipment, the installation equipment, the support plate and the measuring and testing equipment according to Hilti's technical manual.

#### 1.1 Identification of components:

Component name	Designation
F-BT-MR M6x25 SN (4)	Stainless steel stud F-BT-MR SN with sealing washer for thin parent material
F-BT-MR M8x25 SN (4)	Stainless steel stud F-BT-MR SN with sealing washer for thin parent material
F-BT-MR 3/8x1 SN (5/32)	Stainless steel stud F-BT-MR SN with sealing washer for thin parent material
F-BT-MR M6x25 SN (6)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR M8x25 SN (8)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR M10x25 SN (10)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR M10x50 SN (10)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR 3/8x1 SN (3/8)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR 3/8x1-1/2 SN (3/8)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR 3/8x2 SN (3/8)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR 3/8x4 SN (3/8)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR M12x25 SN (10)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR M12x50 SN (10)	Stainless steel stud F-BT-MR SN with sealing washer
F-BT-MR M6x25 (6)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR M8x25 (8)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR M10x25 (10)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR M10x50 (10)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR 3/8x1 (3/8)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR 3/8x1-1/2 (3/8)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR 3/8x2 (3/8)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR 3/8x4 (3/8)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR M12x25 (10)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR M12x50 (10)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR 1/2x1-1/2 (3/8)	Stainless steel stud F-BT-MR without sealing washer
F-BT-MR 1/2x2 (3/8)	Stainless steel stud F-BT-MR without sealing washer

#### 1.2 Materials:

Component	Material
F-BT-MR stud	Stainless steel 1.4571 (A5), 316Ti
Sealing ring, metal cap	Stainless steel 1.4404 (A4), 316L
Sealing ring, elastomer	Chloroprene rubber (CR)

### 2. DOCUMENTS AND DRAWINGS:

Designation	Revision / Date
HILTI CORDLESS STUD FUSION Technical Manual	May 2023

### 3. TEST REPORTS:

According to the following tests:

- Evaluation report no. XE-23-10 at HILTI Aktiengesellschaft, Schaan / LIECHTENSTEIN dd. March 9, 2023
- Test report no. L22/0862\_01 at gbd Lab GmbH, Dornbirn / AUSTRIA dd. 27.07.2022
- Test report no. L22/0862\_02 at gbd Lab GmbH, Dornbirn / AUSTRIA dd. 19.10.2022
- Test report no. L22/0862\_03a at gbd Lab GmbH, Dornbirn / AUSTRIA dd. 13.12.2022
- Test report no. XE\_23\_18 at HILTI Aktiengesellschaft, Schaan / LIECHTENSTEIN dd. March 3, 2023
- Test report no. XE\_22\_17 at HILTI Aktiengesellschaft, Schaan / LIECHTENSTEIN dd. 02 nd May 2022
- Test report no. XE-23-08 at HILTI Aktiengesellschaft, Schaan / LIECHTENSTEIN dd. February 15, 2023

- Test report no. XE\_23\_04 at HILTI Aktiengesellschaft, Schaan / LIECHTENSTEIN dd. 08 th March 2022
- Test report no. PW-2022-0115 at FOCP SPIEZ LABORATORY, Spiez / SWITZERLAND dd. 14.12.2022
- Test report no. PW-2022-0082 at FOCP SPIEZ LABORATORY, Spiez / SWITZERLAND dd. 25.08.2022

#### 4. APPLICATION / LIMITATION:

4.1 The mechanical fastening system is intended for fastening applications in shipbuilding, offshore and crane structures as far as the BUREAU VERITAS Rules are complied with:

- Multi-disciplinary support
- Welded support for cable trays
- Modular support for cable trays
- Individual support
- Welded support for pipe trays
- Modular support for pipes
- Suspending ceiling
- Equipment fastening
- Shipbuilding fastening

4.2 Parent material specification: Subgroup 1.1, 1.2 according to CEN ISO/TR 15608

Standard / application area	Steel grade
EN 10025-2	S235JR +N (or +AR) to S355K2 +N (or +AR)
EN 10025-3	S275N/NL to S355N/NL
ASTM	ASTM A36, ASTM 572 Grade 50
Shipbuilding steel	A, B, D, E, AH 32, DH 32, AH 36, DH 36, EH 36
Carbon equivalent value: $CEV \leq 0.45$	$CEV = C + Mn / 6 + (Cr + Mo + V) / 5 + (Ni + Cu) / 15$

4.3 Thickness of the parent material:

	t,min	t,max
F-BT-MR M6xL SN (4) F-BT-MR M8xL SN (4)	4 mm	30 mm
F-BT-MR M6xL SN (6) F-BT-MR M6xL (6)	6 mm	30 mm
F-BT-MR M8xL SN (8) F-BT-MR M8xL (8)	8 mm	30 mm
F-BT-MR M10xL SN (10) F-BT-MR M10xL (10) F-BT-MR M12xL SN (10) F-BT-MR M12xL (10)	10 mm	30 mm
F-BT-MR 3/8xL SN (5/32)	5/32" / 4 mm	1 1/8" / 30 mm
F-BT-MR 3/8xL SN (3/8) F-BT-MR 3/8xL (3/8) F-BT-MR 1/2xL (3/8)	3/8" / 10 mm	1 1/8" / 30 mm

For F-BT fasteners without sealing washer, which are welded to uncoated parent material, the minimum parent material thickness amounts to 2 mm.

4.4 Stud positioning in parent material:

	Spacing between studs	Edge distance
F-BT-MR M6xL SN (4) F-BT-MR M8xL SN (4) F-BT-MR M6xL SN (6) F-BT-MR M6xL (6) F-BT-MR M8xL SN (8) F-BT-MR M8xL (8) F-BT-MR M10xL SN (10) F-BT-MR M10xL (10) F-BT-MR M12xL SN (10) F-BT-MR M12xL (10)	35 mm	38 mm
F-BT-MR 3/8xL SN (5/32) F-BT-MR 3/8xL SN (3/8) F-BT-MR 3/8xL (3/8) F-BT-MR 1/2xL (3/8)	1 3/8" / 35 mm	1 1/2" / 38 mm

## 4.5 Thickness of the fastened material:

	<b>t,min</b>	<b>t,max</b>
F-BT-MR M6x25 SN (4) F-BT-MR M8x25 SN (4) F-BT-MR M6x25 SN (6) F-BT-MR M8x25 SN (8) F-BT-MR M10x25 SN (10) F-BT-MR M12x25 SN (10)	3.5 mm	10 mm
F-BT-MR M6x25 (6) F-BT-MR M8x25 (8) F-BT-MR M10x25 (10) F-BT-MR M12x25 (10)	4.5 mm	10 mm
F-BT-MR M10x50 SN (10) F-BT-MR M12x50 SN (10)	3.5 mm	20 mm
F-BT-MR M10x50 (10) F-BT-MR M12x50 (10)	4.5 mm	20 mm
F-BT-MR 3/8x1 SN (5/32) F-BT-MR 3/8x1 SN (3/8)	1/8" / 3.5 mm	3/8" / 10 mm
F-BT-MR 3/8x1 (3/8)	3/16" / 4.7 mm	3/8" / 10 mm
F-BT-MR 3/8x1 1/2 SN (3/8) F-BT-MR 3/8x2 SN (3/8) F-BT-MR 3/8x4 SN (3/8)	1/8" / 3.5 mm	3/4" / 20 mm
F-BT-MR 3/8x1 1/2 (3/8) F-BT-MR 3/8x2 (3/8) F-BT-MR 3/8x4 (3/8) F-BT-MR 1/2x1 1/2 (3/8) F-BT-MR 1/2x2 (3/8)	3/16" / 4.7 mm	3/4" / 20 mm

4.6 Hilti's recommendations regarding to the tightening torque and the max. values of tension load, shear load and bending moment are dependent on the size of stud and have to be complied with.

4.7 The manufacturer's assembly instructions and recommendations are to be complied with.

## **5. PRODUCTION SURVEY REQUIREMENTS:**

- 5.1 The mechanical fastening system are to be supplied by **Hilti Corporation** in compliance with the type described in this certificate.
- 5.2 This type of product is within the category HBV of BUREAU VERITAS Rule Note NR320 and as such does not require a BUREAU VERITAS product certificate.
- 5.3 **Hilti Corporation** has to make the necessary arrangements to have its works recognised by BUREAU VERITAS in compliance with the requirements of NR320 for HBV products.
- 5.4 For information, **Hilti Corporation** has declared to BUREAU VERITAS the following production site:  
Threaded stud:  
**Jiaxing Chuangyuan Machinery Manufacturing Co., Ltd., Jiaxing City / CHINA**

## **6. MARKING OF PRODUCT:**

The mechanical fastening system should be clearly identified with:

- Manufacturer's name or logo
- Type designation

## **7. OTHERS:**

7.1 The mechanical fastening systems will be delivered with the relevant documentation / user's guide.

7.2 It is **Hilti Corporation**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

**\*\*\* END OF CERTIFICATE \*\*\***